English

User's Manual
CH5/CH6/CH7
Monitor Hood



<Landscape> <Portrait>

Thank you very much for choosing an EIZO product.
Please read this User's Manual carefully to familiarize you with safe and effective usage procedures.
Please retain this manual for future reference.

⚠PRECAUTIONS

To ensure personal safety and proper maintenance, please read this section.

⚠CAUTION

Do not carry the monitor with the hood attached.
While carrying the monitor, the hood may fall or slip off, which may result in injury or equipment damage.

Do not place any objects on the hood.
If the hood falls or slips off or the monitor falls over, it may result in injury or equipment damage.

Attach only to specified EIZO LCD monitors.
Attach only to specified EIZO LCD monitors. Attaching to other monitors may cause the hood to drop, which may result in injury or equipment damage. For the specified monitors, please visit our website at http://www.eizo.com.

The monitor hood assembling procedure is available from our video site.

【Video site's URL】

http://www.eizo.com/i/hood/

【QR code】

Package Contents

Please contact your local EIZO representative for assistance if any of the listed items are missing or damaged.

Hood components (8 pcs.)



* **Plate (3)** and **plate (6)** are not used in the landscape position.

User's Manual (this manual)

Installation (Landscape)

To use the monitor in the portrait position, go to page 6.

1. Assemble the left and right hoods.

1. Place **plate (2)** on a flat surface such as a desk. Set up **plate (1)** at a right angle, and snap the tab until it clicks (2 positions).
   * It is recommended that the tabs are snapped separately.



2. Assemble **plate (4)** and **(5)** in the same way.

Detachment

Fold the hood at the connecting part.



2. Attach the left and right hoods to the monitor.

1. Face the back side of the monitor toward the front.



2. Align the hooks on the hood with the corresponding holes in the monitor, and then insert the hooks.



3. While holding the monitor from the bottom, press down the hood to fix it firmly.



4. Attach the hood on the other side in the same way.

3. Attach metal fitting (7).



Holes on top (monitor top view)



Insert the front hook of **metal fitting (7)** into the hole on top.



While pulling **metal fitting (7)** forward, insert the back hook of **metal fitting (7)** into the hole on top.

4. Attach cover (8).



Hook **cover (8)** on the top of the hood.



Place **cover (8)** on the top of the hood while aligning the catch on **cover (8)** with the notch on top.



Slide **cover (8)** to the right to close the hood.

Sensor Attachment

When performing calibration, slide **cover (8)** to the right in order to attach the sensor.



Installation (Portrait)

1. Assemble the left and right hoods.

1. Place **plate (2)** on a flat surface such as a desk. Set up **plate (1)** at a right angle, and snap the tab until it clicks (2 positions).
   * It is recommended that the tabs are snapped separately.





2. Assemble **plate (4)** and **(5)** in the same way.
3. Place connected **plate (1)** and **(2)** on a flat surface such as a desk. Set up **plate (3)** at a right angle, and snap the tab until it clicks (2 positions).





4. Assemble **plate (6)** to connected **plate (4)** and **(5)** in the same way.

Detachment

Fold the hood at the connecting part.



2. Attach the left and right hoods to the monitor.

1. Face the back side of the monitor toward the front.



2. Align the hooks on the hood with the corresponding holes in the monitor, and then insert the hooks.



3. While holding the monitor from the bottom, press down the hood to fix it firmly.



4. Attach the hood on the other side in the same way.

3. Attach metal fitting (7).

Use the procedure on page 5 for reference.

4. Attach cover (8).

Use the procedure on page 5 for reference.

Sensor Attachment

When performing calibration, remove **cover (8)** and then attach the sensor.



Specifications / 仕様

● CH5

Dimensions (W) x (H) x (D)	Landscape	653mm (25.7) × 373 mm (14.7) x 225.5 mm (8.9)
	Portrait	410.5mm (16.2) × 635.5mm (25.0) x 225.5mm (8.9)
Weight	Landscape	Approx. 940g (2.07 lbs)
	Portrait	Approx. 1180g (2.6 lbs)

寸法 （幅）×（高さ）×（奥行き）	横置き	653mm×373mm×225.5mm
	縦置き	410.5mm×635.5mm× 225.5mm
質量	横置き	約940g
	縦置き	約1180g

Dimensions/外形寸法

Landscape/横置き

Unit: mm (inch)
単位：mm(インチ)



Portrait/縦置き



● CH6

Dimensions (W) x (H) x (D)	Landscape	552mm (21.7) × 373 mm (14.7) x 225.5 mm (8.9)
	Portrait	361 mm (14.2) × 555 mm (21.9) x 225.5 mm (8.9)
Weight	Landscape	Approx. 840g (1.85 lbs)
	Portrait	Approx. 960g (2.12 lbs)

寸法 （幅）×（高さ）×（奥行き）	横置き	552mm×373mm×225.5mm
	縦置き	361mm×555mm× 225.5mm
質量	横置き	約840g
	縦置き	約960g

Dimensions/外形寸法

Landscape/横置き

Unit: mm (inch)
単位：mm(インチ)



Portrait/縦置き



● CH7

Dimensions (W) x (H) x (D)	Landscape	582.5mm (22.9) × 373 mm (14.7) x 225.5 mm (8.9)
	Portrait	406 mm (16.0) × 555 mm (21.9) x 225.5 mm (8.9)
Weight	Landscape	Approx. 840g (1.85 lbs)
	Portrait	Approx. 960g (2.12 lbs)

寸法 （幅）×（高さ）×（奥行き）	横置き	582.5mm×373mm×225.5mm
	縦置き	406mm×555mm×225.5mm
質量	横置き	約840g
	縦置き	約960g

Dimensions/外形寸法

Landscape/横置き

Unit: mm (inch)
単位：mm(インチ)

Portrait/縦置き



お客様ご相談窓口のご案内

■ 製品に関するお問い合わせ

EIZO コンタクトセンターでは、製品のお取り扱いや機能説明、ご購入に関するお問い合わせ、ご相談を受け付けております。

EIZO コンタクトセンター　　0120-956-812
受付時間：月～金　9：30～17：30（祝日、当社休業日を除く）

■ 故障／修理に関するお問い合わせ

製品の不具合、修理に関しては、EIZO サポート北陸にお問い合わせください。
修理を依頼される際は、故障症状を具体的にご連絡ください。

●問い合わせ受付　TEL：0767-52-7700（代）FAX：0767-52-0202　月曜日～金曜日　9：30 ～ 17：30（祝日、当社休業日を除く）

廃棄について

自治体の指示に従って廃棄してください。

EIZO Corporation
153 Shimokashiwano, Hakusan, Ishikawa 924-8566 Japan
Phone: +81 76 277 6792　Fax: +81 76 277 6793

EIZO Europe GmbH
Helmut-Grashoff-Strasse 18, 41179 Mönchengladbach, Germany
Phone: +49 2161 8210210　Fax: +49 2161 8210150

EIZO株式会社
〒924-8566　石川県白山市下柏野町 153 番地

http://www.eizo.com
http://www.eizo.co.jp

4th Edition-June, 2013　Printed in Japan.

Copyright © 2012-2013 EIZO Corporation All rights reserved.

03V24051D1
(U.M-CH6)